



**Product** Transformation **Colour** 1628069 Manilla

### Product Specifications

Product Number	1628
Product Construction	Tufted Patterned Structured Loop Pile
Yarn System	100% Solution Dyed Nylon contains recycled content
Standard Backing	Graphlex®
Optional Backing(s) ( <a href="#">Learn more</a> )	ReCushion Bac®, SONE®, CircuitBac Green
Size – Packaging	50 x 50 cm – 4 m <sup>2</sup> Box
Pile Yarn Weight	576 g/m <sup>2</sup> ± 5%
Total Weight	3760 g/m <sup>2</sup> ± 5%
Pile Height	3.3 mm +15% / - 10%
Total Thickness	6.3 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/12 - 47.2
Tufts per m <sup>2</sup>	167,560/m <sup>2</sup> ±5%

### Performance Specifications

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)					
Light Fastness	≥6 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	55.4			23.32		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	25 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.20					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.01	0.05	0.08	0.22	0.34	0.44

### Environmental Specifications

Total Recycled Content	51.1%
Pre-Consumer (Total)	49.6%
Post-Consumer (Total)	1.5%
Yarn Recycled Content	75%
Pre-Consumer (Yarn)	65%
Post-Consumer (Yarn)	10%
Indoor Air Quality	GUT Prodis ID FB53AAD0 <a href="#">M1 Emission Certification - 2</a> French A+ <a href="#">Danish Indoor Climate</a> <a href="#">GLP 9819</a> <a href="#">GUI Standard</a>
Potential Green Building Contribution	
BREEAM (UK/International)	<a href="#">View potential BREEAM contribution</a>
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>
HQE (France)	<a href="#">View Potential HQE Contribution</a>
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>
Environmental Product Declaration	<a href="#">wc_epd-int-20180117-transformation-cbc1-en</a>

### Installation Method



Non Directional

Interface European Manufacturing BV reserve the right to change or modify specifications.

<b>Carbon Footprint</b>	
Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Cradle-To-Gate (Raw Materials and Production)	9.25 kg CO <sub>2</sub> eq./m <sup>2</sup>
Carbon Neutral Floors™	Standard
<b>Installation Impacts</b>	
Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below: Non-directional – 1-2% For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
<b>End of Life Options</b>	
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

**Technical Information**

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001, 14001 &amp; 45001 Certified Facilities in Europe</a>

**Performance Qualifications**



**Certifications**

